




Cone 1

Unilamp IP54 post top luminaire

Black / Graphite / Dark Grey / Aluminium Silver / White

Ø 380 H 3500	42W TC-TE GX24q-4	7203-0-3-436
Ø 380 H 3500	70W HCI-E/P E27	7203-0-3-711
Ø 380 H 3500	70W HPS E27	7203-0-3-611
Ø 380 H 3500	80W HQL E27	7203-0-3-511



7203-0-3-711

Anchor Bolt Kit

Unilamp anchor bolt kit for bollards and post top lights. For concrete foundation installation

Head Dimensions

For Cone, Helios, Maranello, Stick, Pillar, Rector **9-2020-00**

Root Mount Kit

Unilamp anchor bolt kit for bollards and post top lights. For ground installation

Head Dimensions

For Cone, Helios, Maranello, Stick, Pillar, Rector **9-2060-00**

Head components in corrosion resistant cast and spun aluminium. Other components in corrosion resistant, low copper extruded aluminium. UV stabilised high heat resistant clear with partly prismatic PMMA diffuser. UV stabilised high heat resistant clear with partly prismatic PMMA diffuser. Different column height can be made upon request

Unilamp Pole

Black / Graphite / Dark Grey / Aluminium Silver / White

For Cone, Helios and Maranello. (Corrosion and impact resistant extruded aluminium pole)

H 2000 Ø 105	9-1001
H 2500 Ø 105	9-1002
H 3000 Ø 105	9-1003
H 3500 Ø 105	9-1004
H 4000 Ø 105	9-1005

For Sirocco and Match Box. With modification can be used for Cone, Helios and Maranello. (Hot dipped galvanised steel pole)

H 4000 Ø 102	9-1021
H 5000 Ø 102	9-1023
H 6000 Ø 102	9-1025

*Die cast aluminium service door and mounting base with stainless steel fastner
Coated with polyester powder with UV stabilised additive*

