



Helios


Unilamp IP65 indirect post top luminaire

Black / Graphite / Dark Grey / Aluminium Silver / White


Head Dimensions

W 1000 H 1090	35W HCI-T G12	7221-7-3-751
W 1000 H 1090	70W HCI-T G12	7221-7-3-752
W 1000 H 1090	150W HCI-T G12	7221-7-3-753


Head components and wall bracket in high pressure die-cast aluminium. Other components in corrosion resistant, low copper extruded aluminium
Mounting kits and poles available on page 152



7221-7-3-751



7221-7-3-752



7221-7-3-753

Unilamp Pole

Black / Graphite / Dark Grey / Aluminium Silver / White

For Cone, Helios and Maranello. (Corrosion and impact resistant extruded aluminium pole)

H 2000 Ø 105	9-1001
H 2500 Ø 105	9-1002
H 3000 Ø 105	9-1003
H 3500 Ø 105	9-1004
H 4000 Ø 105	9-1005

For Sirocco and Match Box. With modification can be used for Cone, Helios and Maranello. (Hot dipped galvanised steel pole)

H 4000 Ø 102	9-1021
H 5000 Ø 102	9-1023
H 6000 Ø 102	9-1025

Die cast aluminium service door and mounting base with stainless steel fastener
Coated with polyester powder with UV stabilised additive

Anchor Bolt Kit

Unilamp anchor bolt kit for bollards and post top lights. For concrete foundation installation

Head Dimensions

For Cone, Helios, Maranello, Stick, Pillar, Rector **9-2020-00**

Root Mount Kit

Unilamp anchor bolt kit for bollards and post top lights. For ground installation

Head Dimensions

For Cone, Helios, Maranello, Stick, Pillar, Rector **9-2060-00**

