



Maranello

Unilamp IP65 indirect post top luminaire

Black / Graphite / Dark Grey / Aluminium Silver / White

Head Dimensions

W 809 H 955	35W HCI-T G12	7222-7-3-751
W 809 H 955	70W HCI-T G12	7222-7-3-752
W 809 H 955	150W HCI-T G12	7222-7-3-753

Head components and wall bracket in high pressure die-cast aluminium. Other components in corrosion resistant, low copper extruded aluminium

Unilamp Pole

Black / Graphite / Dark Grey / Aluminium Silver / White

For Cone, Helios and Maranello. (Corrosion and impact resistant extruded aluminium pole)

H 2000 Ø 105	9-1001
H 2500 Ø 105	9-1002
H 3000 Ø 105	9-1003
H 3500 Ø 105	9-1004
H 4000 Ø 105	9-1005

For Sirocco and Match Box. With modification can be used for Cone, Helios and Maranello. (Hot dipped galvanised steel pole)

H 4000 Ø 102	9-1021
H 5000 Ø 102	9-1023
H 6000 Ø 102	9-1025

Die cast aluminium service door and mounting base with stainless steel fastner Coated with polyester powder with UV stabilised additive

Anchor Bolt Kit

Unilamp anchor bolt kit for bollards and post top lights. For concrete foundation installation

Head Dimensions


For Cone, Helios, Maranello, Stick, Pillar, Rector 9-2020-00

Root Mount Kit


Unilamp anchor bolt kit for bollards and post top lights. For ground installation

Head Dimensions


For Cone, Helios, Maranello, Stick, Pillar, Rector 9-2060-00



7222-7-3-751



7222-7-3-752



7222-7-3-753

