




**Medium Sirocco Area Light Asymmetric**

Unilamp IP65 asymmetric area light with impact resistant clear safety tempered glass


Black / Graphite / Dark Grey / Aluminium Silver / White

*Head Dimensions*

W 380 H 180 D 550	150W HCI-TT E40	7250-1-3-722 (concentrated)
W 380 H 180 D 550	150W HCI-TT E40	7250-2-3-722 (diffused)
W 380 H 180 D 550	250W HCI-TS FC2	7250-1-3-733 (concentrated)
W 380 H 180 D 550	250W HCI-TS FC2	7250-2-3-733 (diffused)



7250-2-3-722



7250-2-3-733

**Anchor Bolt Kit**

Unilamp anchor bolt kit for bollards and post top lights. For concrete foundation installation

*Head Dimensions*

For Cone, Helios, Maranello, Stick, Pillar, Rector **9-2020-00**

**Root Mount Kit**

Unilamp anchor bolt kit for bollards and post top lights. For ground installation

*Head Dimensions*

For Cone, Helios, Maranello, Stick, Pillar, Rector **9-2060-00**

Body in high pressure die-cast aluminium

**Unilamp Pole**

Black / Graphite / Dark Grey / Aluminium Silver / White

*For Sirocco and Match Box. With modification can be used for Cone, Helios and Maranello. (Hot dipped galvanised steel pole)*

H 4000 Ø 102	<b>9-1021</b>
H 5000 Ø 102	<b>9-1023</b>
H 6000 Ø 102	<b>9-1025</b>

*For Sirocco and Match Box. (Hot dipped galvanised steel pole)*

H 6000 Ø 120	<b>9-1036</b>
H 7000 Ø 120	<b>9-1037</b>
H 8000 Ø 120	<b>9-1038</b>
H 9000 Ø 120	<b>9-1039</b>

*Die cast aluminium service door and mounting base with stainless steel fastner  
Coated with polyester powder with UV stabilised additive*