Type A

Mega Sonic Gear

Unilamp IP65 wall or ground mount spotlight with impact resistant clear safety tempered glass and integral electronic control gear

Black / Graphite / Dark Grey / Aluminium Silver / White

Without Arm

Ø 185 **H** 262 **D** 370	70W HCI-T G12	5935-5-3-781 (narrow beam)
Ø 185 **H** 262 **D** 370	70W HCI-T G12	5935-6-3-781 (medium beam)
Ø 185 **H** 262 **D** 370	150W HCI-T G12	5935-5-3-782 (narrow beam)
Ø 185 **H** 262 **D** 370	150W HCI-T G12	5935-6-3-782 (medium beam)

With Arm

Ø 185 **H** 262 **D** 1063	70W HCI-T G12	5936-5-3-781 (narrow beam)
Ø 185 **H** 262 **D** 1063	70W HCI-T G12	5936-6-3-781 (medium beam)
Ø 185 **H** 262 **D** 1063	150W HCI-T G12	5936-5-3-782 (narrow beam)
Ø 185 **H** 262 **D** 1063	150W HCI-T G12	5936-6-3-782 (medium beam)

Base Dimensions: **L** 206 **W** 136 **D** 89

Body in corrosion resistant high pressure die-cast aluminium



5935-5-3-782



5935-6-3-782